



TYPICAL SECTION

NOTES:

POST SPECIFICATION:
 GALVANISED STAR PICKETS 1650mm LENGTH.
 IN SOFT GROUND POSTS SHOULD BE 1800mm LENGTH.
 IN SWAMP AFFECTED AREAS USE RECYCLED PLASTIC
 POSTS 100 DIA.

BARBED WIRE SPECIFICATIONS:
 LONGLIFE HIGH TENSILE BARBED WIRE 1.57mm DIAMETER
 MINIMUM BREAKING STRAIN: 3kN
 RECOMMENDED TENSION: 1.3kN

NOTE: IN AREAS AT RISK OF BUSH FIRE USE LONGLIFE
 BARBED WIRE 2.5mm DIAMETER
 MINIMUM BREAKING STRAIN: 3kN
 RECOMMENDED TENSION: 1.3kN

WIRE FASTENING SPECIFICATIONS:
 POST CLIPS 3.15mm LONGLIFE COATED WIRE

WIRE TENSIONING SPECIFICATIONS:
 RATCHET STYLE IN LINE ADJUSTER

WIRE TIE OFF SPECIFICATIONS:
 MINIMUM 300mm WIRE TWIST RETURN
 LENGTH TO POSTS & STRAINERS

STRAINER POST SPECIFICATIONS:
 REFER GCCC STD DWG No. 05-603

ALL MEASUREMENTS ARE IN MILLIMETRES
 UNLESS STATED OTHERWISE

ACCESS TO CONSTRUCTION AREA:
 ACCESS TO THE SITE MAY REQUIRE 4 WHEEL DRIVE VEHICLES ONLY.
 SOME SITES MAY REQUIRE THE NEED TO WALK MATERIALS IN FOR A
 SHORT DISTANCE.

TERRAIN:
 SOME SITES WILL NOT BE ON A FLAT SURFACE. TOPOGRAPHY,
 TERRAIN AND DIGGING CONDITIONS ARE VARIABLE.

WORKMANSHIP AND MATERIALS TO BE IN ACCORDANCE WITH AS2423,
 AS1725, AS4100 AND OTHER RELEVANT AUSTRALIAN STANDARDS.

Gold Coast City Council
 GOLD COAST CITY COUNCIL
 PO BOX 5042
 GOLD COAST MC 9729

THIS DRAWING IS NOT TO BE AMENDED WITHOUT REFERENCE TO STANDARDS COMMITTEE			
No.	AMENDMENT	APPROVED	DATE

CONTROLLED DOCUMENT
ISSUED

DO NOT SCALE TAKE FIGURED DIMENSIONS ONLY	
DRAFTING BY TECHNICAL SERVICES BRANCH	
PASSED - COORDINATOR OPEN SPACE ASSETS	
SIGNED:	DATE: 6/12/12
NAME: CAMERON TAYLOR	
APPROVED - MANAGER PARKS & RECREATIONAL SERVICES	
SIGNED:	DATE: 6/12/12
NAME: RON JACOBS	

STANDARD DRAWING

**STAR PICKET & WIRE STRAND FENCING
TYPE 1 (STOCK FENCE)**

MICROFILMED
STANDARD DRAWING No. 13-05-601
ISSUE 2013 EDITION