



NOTES

1. FOR CONSTRUCTION DETAILS REFER TO G.C.C.C. STD. DWG. Nos. 08-07-125 TO 08-07-127 AND 08-07-136 TO 08-07-138.
2. THE SUPPLY AND INSTALLATION OF PUMPS, RISER PIPES, BENDS AND ALL ASSOCIATED FITTINGS SHALL COMPLY WITH COUNCILS STANDARD SPECIFICATION SS1.
3. THE RISER PIPE SHALL BE ϕ LIGHT CEMENT LINED DUCTILE IRON FLANGE CLASS UNLESS OTHERWISE APPROVED BY COUNCIL.
4. THE LIFT STATION DIAMETER AND LID DIMENSIONS HAVE BEEN DETERMINED ON THE BASIS OF USE OF THE FOLLOWING TYPE, SIZE AND VOLUTE DIAMETER OF PUMPS.....
5. THE HIGHEST RECORDED FLOOD LEVEL AS SUPPLIED BY COUNCIL IS R.L.
6. THE PROTECTIVE COATING SYSTEM SHALL BE.....

THIS DRAWING IS TO BE COMPLETED BY THE CONSULTANT AND SHALL FORM PART OF THE ENGINEERING DRAWINGS SUBMITTED TO COUNCIL FOR APPROVAL



Gold Coast City Council
 GOLD COAST CITY COUNCIL
 PO BOX 5042
 GOLD COAST MC 9729

THIS DRAWING IS NOT TO BE AMENDED WITHOUT REFERENCE TO STANDARDS COMMITTEE				CONTROLLED DOCUMENT	DO NOT SCALE TAKE FIGURED DIMENSIONS ONLY
					DRAWN BY G.C.W
					PASSED D. HAYMAN 08/07/08
					APPROVED R. WENT 08/07/08
No.	AMENDMENT	APPROVED	DATE	ISSUED	

STANDARD DRAWING

**SEWERAGE LIFT STATION
 DIAGRAMATIC LAYOUT**

MICROFILMED
STANDARD DRAWING No. 08-07-138
ISSUE 2008 EDITION